

Aging of Cable Rubber Insulation

75674
SOV/80-32-10-23/51

The activation energy of the aging process can be determined from the Arrhenius equation using the experimental values of the oxidation rate constants at two different temperatures. Subsequently, the oxidation rate constants at operational temperature can be determined from equation

$$\lg K_x = \lg K_1 - \frac{E}{4.6} \frac{(T_1 - T_x)}{T_1 \cdot T_x}, \quad (2)$$

where K_1 and K_x are oxidation rate constants at T_1 and T_x , respectively; E is the activation energy (in cal/mole); T_1 is the absolute temperature corresponding to artificial aging conditions; and T_x is the temperature corresponding to normal aging conditions. The actual aging proceeds more quickly than artificial aging, and this is expressed by the correction factor

Card 4/9

Aging of Cable Rubber Insulation

75674
SOV/80-32-10-23/51

K_g which varies in the range of $1.0 \cdot 10^{-4}$ to $6.0 \cdot 10^{-4}$.
Accordingly,

$$K_{\text{total}} = K_x + K_g \quad (3)$$

and the final form of Eq. (1) can be written as

$$\lg(t_f - t_{\infty}) = \lg(t_0 - t_{\infty}) - \left(\frac{K_x + K_g}{2.3} \right) t. \quad (4)$$

Aging time t_{kp} and the corresponding ϵ_{kp} can be determined from Eq. (4) and the curves in Fig. 2, and can be used as a guide to establish the guaranteed life of a cable. Correcting factors must be introduced, however, to account for the construction and size of the cable, ambient humidity, biological medium, kind of core metal, etc., etc. Values of the relative elongation at the moment of rupture for both rubber types were calculated for up to 3,650 days of aging and checked against experimental values for up to

Card 5/9

Aging of Cable Rubber Insulation

75674
SOV/80-32-10-23/51


915 days. Migration of copper into rubber, and migration of thiuram, sulfur, plasticizers, and other compounds was investigated. Thiuram migrated from the internal core insulation into the external rubber sleeve, and accelerated its aging. Copper compounds migrating from the cable core into the insulation had the same effect on the internal insulation. A method is suggested for the determination of the time of moistening of rubber as function of temperature, sleeve thickness, and electrical breakdown constant. Rubber disks 1 mm thick, and 110 mm in diameter were placed in sleeve rubber envelopes 1 mm and 2 mm thick. The disks were placed above water in a container with water maintained at a given temperature. After a predetermined period of time the disks were removed from the container, freed from the envelope, and tested for electric breakdown according to GOST 2068-54 and 6433-52. The study was made under supervision of Sokolov, S. I., and directions of Lyubchanskaya, L. I., and Kuz'minskiy, A. S. There are 8 figures; 2 tables; and 10 references, 1 German, 9 Soviet.

Card 6/9

Aging of Cable Rubber Insulation

75674
30V/80-32-10-23/51

Caption to Fig. 8
on card 8/9.



Card 7/9

Aging of Cable Rubber Insulation

75674
SOV/80-32-10-23/51

Caption to Figure 8.

Fig. 8. Relation between the breakdown voltage of insulation rubber and the time of moistening through rubber sleeve 1 mm thick at 20° and 70°. A, breakdown voltage (in v/mm.); B, time of moistening (in days). At 20°: (1) ShN-40 rubber; (2) ShBM-40 rubber; (3) butyl rubber base compound; at 70°: (4) ShN-40 rubber; (5) ShBM-40 rubber; (6) butyl rubber. Moistening: (I) at 20°; (II) at 70°.

Card 8/9

Aging of Cable Rubber Insulation

75674

SOV/80-32-10-23/51

Caption to Figure 8.

Fig. 8. Relation between the breakdown voltage of insulation rubber and the time of moistening through rubber sleeve 1 mm thick at 20° and 70°. A, breakdown voltage (in v/mm.); B, time of moistening (in days). At 20°: (1) ShN-40 rubber; (2) ShBM-40 rubber; (3) butyl rubber base compound; at 70°: (4) ShN-40 rubber; (5) ShBM-40 rubber; (6) butyl rubber. Moistening: (I) at 20°; (II) at 70°.

Card 8/9

Aging of Cable Rubber Insulation

75674
SOV/80-32-10-23/51

ASSOCIATION: Scientific Research Institute of Cable Industry (Nauchno-
issledovatel'skiy institut kabel'noy promyshlennosti)

SUBMITTED: June 25, 1959, for the second time

Card 9/9

DUBROVIN, G.V..

Strut for tie repairs. Put' i put. khos. 4 no. 12:29 D '60.
(MIRA 13:12)

1. Tekhnik po opytu rabotam Pushkinskoy distantsii puti
Moskovskoy dorogi.
(Railroads--Equipment and supplies)

"APPROVED FOR RELEASE: 08/25/2000


CIA-RDP86-00513R000411410015-4

DUBROVIN, I., insh.; SAFRONOV, V., insh.

Petroleum fleet operations according to the principle of
permanently attaching tows to the barges. Rech.transp. 19 no.5
10-12 My '60. (MIRA 13:7)
(Tank vessels) (Tugboats)

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"



Effect of high temperatures on arsenic salts of lead and
tin. I. M. Dubrovskij. *J. Applied Chem. (U. S. S. R.)*
9, no. 3270-3271 (1951).—*Zn arsenite* is stable
up to 610°. At 610-800° thermal dissociation takes place,
but the valence of As remains unchanged. Above 800°
the possible reactions are: oxidation-reduction, thermal
dissociation, and oxidation by O of the air. At 850-875°
oxidation by air is at its max., while at 700° oxidation-
reduction is predominant. Pb arsenite begins to dissociate
thermally at 250-300°; this is accompanied by oxidation
of As by air. At 550° all As is oxidized to the quinque-
valent state. At 700° oxidation with O of the air is at
its max.; while thermal dissociation decreases and cannot be
detected at 800° or above. At 1000° partial decomposition of
the Pb arsenite formed begins. Zn arsenite does not de-
compose up to 810° and Pb arsenite up to 850-1000°.
V. A. Kalichevsky

١٥

a-1

Formation of ammonium salts with addition of
silver nitrate at high temperatures. J. M.
Dowd, U. S. Appl. Chem. Inst., 1906, 9, 1002.
Formation of Ag_2O begins to commence with AgNO_3 at 200° ,
and of Ag_2O_2 the decomposition of $\text{Ag}_2(\text{NO}_3)_2$ is at a max.
 Ag^+ is absent. At 200° Ag^{+} and Ag^{\bullet} are present
in approx. equal amounts, but the total Ag content
is at a minimum at 200° . Mixtures heated
at 200° contain no Ag^+ ; with rising temp. above 200°
the silver ion concentration rises to a max. at 700° ,
thereafter decreasing. Formation of $\text{Fe}_2/\text{Ag}_2\text{O}_2$ is
complete at 200° , and is accompanied with oxidation
to $\text{Fe}_2(\text{NO}_3)_3$ (Fe^{2+} at 200° - 250°); with rising temp.
the oxygen concentration As falls to a min. at 200° -
 250° (max. of Ag_2O_2 by formation), whilst at 400° -
 500° the silver content reaches a maximum of $(1/2)$. Com-
bination commences with oxidation of Ag^{+} to Ag^{\bullet} ,
taking place between Fe_2O_3 and Ag_2O_2 at 250° , and is
at a max. at 500° ; with rising temp. above 500°
the content of oxidized Ag falls to a min. at 600° ,
due to thermal decomposition; and then rises to a const.
level at 600 - 700° , where conductively Ag^+ is present.

B.C.

Behavior of arsenic anhydride volatilized together with other oxides in hot gases. I. M. Dvornitsyn. Appl. Chem. Russ., 1934, 6, 2143-2144.—The amount of non-volatile As oxide formed when air containing As_2O_3 is mixed with air containing As_2O_3 at $400^\circ \text{K} > 96.5\%$, and also in presence of SO_2 and/or H_2O is < 1% by volume. In presence of PbO fumes formation of non-volatile As^{+11} and As^+ oxides at $250^\circ \text{K} > 98.4\%$, and is inhibited by H_2O at 400°K and increased at 500°K . NO_x inhibits sulfide formation.


AIA-EUR METALLURGICAL LITERATURE CLASSIFICATION


CLASSIFICATION	SEARCHED	SEARCHED	SEARCHED
GENERAL	SEARCHED	SEARCHED	SEARCHED

The process of distillation of zinc occurs in the reverberatory furnaces at the lead smelting works of Chinkiang. I. M. D. Duggar, *Trans. Metall. Soc.*, 12, No. 10, 51-62 (1927); *Zhur. Zavod.*, 1408, II, 755; cf. C. A. 23, 4357. Distillations observed in operation, which are caused by a relatively high Cu content and the presence of Zn, predominantly in the oxidized condition, in the dry zinc, are discussed. In order to prevent them it is recommended that the ZnO be thoroughly reduced during refining, that a reducing agent (e. g., wood charcoal) in finely divided form be introduced, that the furnace temp. be kept below 130°, and that the fuel oil be dried as thoroughly as possible. M. G. Moore

STRUCTURE OF FABRICATED LITERATURE CLASSIFICATION

APPROVED FOR RELEASE: 08/25/2000 CIA-RDP86-00513R000411410015-4"





CR
9

The working up of slag from the smelting of copper in water-jacketed furnaces in the Meceray Molybdenum Works, Lead, Nebraska. Trans. Inst. Min. Metall., 19, No. 11, pt. 2 (1900); Chem. Zentral, 1900, II, 2171; cf. C. A. 34, 6785. The following figures are given for the recovery of Cu: The Cu in the melt, 81%; Cu in the dust, 81%; Cu in the flux, 79%; Cu in the slag, 69%. From 4 to 10% of coke and 13% of magnetic pyrites (tailed, on the granulated slag) were used. By the addition of magnetic pyrites (or better Fe pyrites) the Cu content of the melt was held to a max. of 11%. The slag should contain about 20% or somewhat more CuO. The temp. of the blast-furnace gas was about 700°; the gas contained 7-15% CH₄, 0.04% H₂ and 3.5-11% CO. The slag should be drawn off with a temp. of at least 1200°.

M. G. Moore

11(7),5(2)

AUTHORS:

Dubrovin, I. M., Yevseyev, A. K.

SOV/99-7-4-14/28

TITLE:

The Thermodynamics of the Reduction of Uranium Tetrafluoride
by Magnesium

PERIODICAL:

Atomnaya energiya, 1959, Vol 7, Nr 4, pp 379-382 (USSR)

ABSTRACT:

A system consisting of condensed phases (uranium, magnesium fluoride, uranium tetrafluoride) and magnesium vapor may be considered to be monovariant at the temperature of thermal magnesium reduction ($\sim 1400^{\circ}\text{C}$) if a certain reciprocal solubility of its components is neglected. In this case the constants of reaction equilibrium at various temperatures may be determined from the equation of the isothermal line of the reaction:

$$\Delta F^\circ = -4.576 T \lg K \quad \text{or} \quad \Delta F^\circ = -4.576 T \lg(1/P_{\text{Mg}}^2).$$

Here, P_{Mg} denotes the equilibrium pressure of the magnesium vapors. The variations ΔF_T° of the free energy of the reaction were determined for various temperature intervals from the Gibbs-Helmholtz-equation. When determining the variation of free energy the following phase transformations were taken into

Car: 1/3

The Thermodynamics of the Reduction of Uranium
Tetrafluoride by Magnesium

SOV/89-7-4-14/28

account: (1) The melting of magnesium at the temperature of 923°K . (2) The transition of α -uranium into β -uranium at 938°K . (3) The transition of β -uranium into γ -uranium at 1045°K . (4) The melting of UF_4 at $1,309^{\circ}\text{K}$. (5) The boiling of the magnesium at $1,374^{\circ}\text{K}$. (6) The melting of the uranium at $1,406^{\circ}\text{K}$. (7) The melting of MgF_2 at $1,536^{\circ}\text{K}$. The results of the computations are compiled in a table in form of equations for the variation of the free energy of the reaction. The smoothed values of this variation ΔF° are shown by a diagram. The third table shows the numerical values of ΔF° , $\lg K$, and P_{Mg} for the characteristic temperatures, and, for comparison, the results of other calculations of ΔF° . According to these results, the reduction of UF_4 by magnesium at $1,400^{\circ}\text{C}$ develops practically completely in the direction of the side at which metallic uranium and MgF_2 are produced, because the equilibrium pressure of the magnesium vapors is very low at this temperature (0.8 torr). The higher the magnesium vapor pressure in the closed reaction

Card 2/3

The Thermodynamics of the Reduction of Uranium
Tetrafluoride by Magnesium

307/89-7-4-14/28

apparatus (in the closed vessel), the more rapid and complete will be the reduction. In the case of an excess (0.5% to 10%) of magnesium in the melting stock its vapor pressure in the bomb amounts to 8 atmospheres at 1,400°. If black uranium is remelted (refined) (~1,400°C) in vacuum (which is higher than the magnesium vapor pressure corresponding to equilibrium for the reduction) a reaction develops in the inverse direction between the black uranium and the slag inclusions of MgF_2 .

In this case separation of uranium from MgF_2 is brought about more completely by the volatilization of the produced magnesium and of UF_4 . There are 1 figure, 3 tables, and 11 references, 4 of which are Soviet.

SUBMITTED: April 9, 1959

Card 3/3

85568

S/089/60/009/005/013/020
B025/B070

21.3100

AUTHORS: Dubrovin, I. M., Yevseyev, A. K.

TITLE: Thermodynamics of the Reduction of the Fluorides of Potassium and Sodium by Metallic Calcium and Magnesium

PERIODICAL: Atommaya energiya, 1960, Vol. 9, No. 5, pp. 414 - 417

TEXT: Impurities of potassium and sodium occur in uranium tetrafluoride mostly in the form of fluorides. They disturb the reaction of uranium and decrease its yield. It is with a view to study these disturbing effects that the change of the thermodynamic potential ΔF°_T in the reactions quoted in Table 2 has been calculated for different intervals of temperature, starting data being taken from Table 1. The calculated temperature dependence of the free energy of potassium and sodium fluorides on reaction with calcium and magnesium is represented in the attached diagram. The conclusion is that in the fusion reduction of uranium tetrafluoride the admixtures of alkali metals must be as low as possible. There are 1 figure, 2 tables, and 9 references:

Card 1/6

85568
Thermodynamics of the Reduction of the
Fluorides of Potassium and Sodium by
Metallic Calcium and Magnesium

S/089/60/009/005/013/020
B025/B070

5 Soviet, 1 US, and 3 British.

SUBMITTED: February 29, 1960

Card 2/6

85568

Table 1

S/089/60/009/005/013/020
E025/B070

Термодинамическая величина и ее размерность	Компонент реации	Значение термодинамической величины	Литера- тура	Теплоемкость С _p , кДж/моль·град	Температурный интервал С _p , °К	Литера- тура для С _p
ΔF ₁₂₃ , кДж/моль	NaF	-129,3	[2]	—	—	—
ΔF ₁₂₃ , 0 0	KF	-127,4	[3]	—	—	—
ΔF ₁₂₃ , 0 0	CaF ₃	-277,7	[2]	—	—	—
ΔH ₁₂₃ , кДж/моль	NaF	-136,0	[2]	—	—	—
ΔH ₁₂₃ , 0 0	KF	-134,5	[3]	—	—	—
ΔH ₁₂₃ , 0 0	CaF ₃	-290,3	[2]	—	—	—
ΔS ₁₂₃ , кДж/моль·град	NaF	14,0	[3]	10,79+4,2·10 ⁻³ T	273—1265	[4]
ΔS ₁₂₃ , 0 0	KF	15,91	[3]	11,27+3,86·10 ⁻³ T— -0,69·10 ⁴ ·T ⁻¹	330—600	[4]
ΔS ₁₂₃ , 0 0 0	CaF ₃	16,46	[3]	13,8+7,8·10 ⁻³ T	298—1424	[4]
ΔS ₁₂₃ , 0 0 0	Na	12,2	[3]	5,01+5,36·10 ⁻³ T	298—371	[4]
ΔS ₁₂₃ , 0 0 0	K	15,2	[3]	5,24+5,55·10 ⁻³ T	273—336,5	[4]
ΔS ₁₂₃ , 0 0 0	Ca	9,95	[3]	5,31+3,33·10 ⁻³ T	273—713	[4]
ΔH ₁₂₃ , кДж/моль	α Ca → → β Ca	0,24	[4]	1,5+7,74·10 ⁻³ T+ +2,5·10 ⁴ ·T ⁻¹	750—1123	[4]
ΔH ₁₂₃ , 0 0	α CaF ₃ → → β CaF ₃	1,14	[3]	25,81+2,5·10 ⁻³ T	1424—1691	[4]
ΔH ₁₂₃ , кДж/моль	NaF	7,8	[4]	16,0	>1256	[5]
ΔH ₁₂₃ , 0 0	KF	6,3	[4]	16,7	>1159	[5]
ΔH ₁₂₃ , 0 0 0	CaF ₃	7,1	[3]	23,85	1691—1800	[4]
ΔH ₁₂₃ , 0 0 0	Na	0,63	[4]	7,5	371—450	[4]
ΔH ₁₂₃ , 0 0 0	K	0,57	[4]	7,7	336,5—373	[4]
ΔH ₁₂₃ , 0 0 0	Ca	2,2	[3]	7,4	1123—1223	[4]
ΔH ₁₂₃ , кДж/моль	Na	23,4	[4]	4,07	>1150	[3]
ΔH ₁₂₃ , 0 0 0	K	19,0	[4]	4,97	>1048	[3]
ΔH ₁₂₃ , 0 0 0	Ca	34,8	[6]	4,07	1713	[3]

Card 3/6

85568

S/089/60/009/005/013/020
B025/B070

Legend to Table 1:

- 1) Thermodynamical quantity and its dimension
- 2) Components of reaction
- 3) Value of the thermodynamical quantity
- 4) References
- 5) Specific heat C_p (cal/mole.deg)
- 6) Temperature interval for C_p
- 7) References for C_p

Card 4/6

85568

S/089/60/009/005/013/020
B025/B070.ΔF_T, kcal/mole

1) Интервал температур, "К"

$$\begin{aligned}
 & 2\text{NaF} + \text{Ca} = 2\text{Na} + \text{CaF}_2 \\
 298-371 & -17,690 - 21,4T - 3,4 \cdot 10^{-3}T^2 + 7,06T \lg T \\
 371-713 & -17,540 + 5,64T + 1,97 \cdot 10^{-3}T^2 - 4,39T \lg T \\
 713-1123 & -19,730 + 31,9T + 4,17 \cdot 10^{-3}T^2 + 1,25 \cdot 10^4T^{-1} - 13,14T \lg T \\
 1123-1156 & -19,820 - 5,07T + 0,3 \cdot 10^{-3}T^2 + 0,43T \lg T \quad \text{Table 2} \\
 1156-1265 & 32,840 - 86,29T + 0,3 \cdot 10^{-3}T^2 + 12,08T \lg T \\
 1265-1424 & 23,700 - 148,1T - 3,9 \cdot 10^{-3}T^2 + 36,05T \lg T \\
 1424-1691 & 13,100 - 57,48T - 1,25 \cdot 10^{-3}T^2 + 8,42T \lg T \\
 1691-1713 & 27,010 - 82,13T + 12,86T \lg T \\
 1713-1977 & -11,960 - 41,3T + 7,26T \lg T
 \end{aligned}$$



$$\begin{aligned}
 298-336,5 & -20,200 - 27,39T - 3,93 \cdot 10^{-3}T^2 - 0,69 \cdot 10^4T^{-1} + 8,2T \lg T \\
 336,5-713 & -20,090 - 1,1T + 1,63 \cdot 10^{-3}T^2 - 0,69 \cdot 10^4T^{-1} - 3,1T \lg T \\
 713-1048 & -22,290 + 25,16T + 3,83 \cdot 10^{-3}T^2 + 0,56 \cdot 10^4T^{-1} - 11,85T \lg T \\
 1048-1123 & 21,440 - 54,3T + 3,83 \cdot 10^{-3}T^2 + 0,56 \cdot 10^4T^{-1} + 0,75T \lg T \\
 1123-1159 & 21,350 - 51,17T - 0,04 \cdot 10^{-3}T^2 - 0,69 \cdot 10^4T^{-1} + 14,32T \lg T \quad \text{Card 5/6}
 \end{aligned}$$

85568

1159-1424
1424-1691
1691-1713
1713-1775

	$16\ 060 - 158,63T - 3,9 \cdot 10^{-3}T^2 + 39,32T \lg T$	S/089/60/009/005/013/020
	$5\ 600 - 68,02T - 1,25 \cdot 10^{-3}T^2 + 11,77T \lg T$	B025/B070
	$19\ 370 - 92,67T + 16,14T \lg T$	
	$- 19\ 000 - 51,84T + 10,54T \lg T$	
	 $2\text{NaF} + \text{Mg} = 2\text{Na} + \text{MgF}_2$	
298-371	$7530 - 0,18T - 1,29 \cdot 10^{-3}T^2 + 1,28 \cdot 10^4 \cdot T^{-1} + 0,02T \lg T$	
371-923	$7680 + 26,85T + 4,03 \cdot 10^{-3}T^2 + 1,28 \cdot 10^4 \cdot T^{-1} - 11,43T \lg T$	
923-1150	$7180 + 0,61T + 2,85 \cdot 10^{-3}T^2 + 1,33 \cdot 10^4 \cdot T^{-1} - 5,06T \lg T$	
1150-1265	$59\ 830 - 71,61T + 2,85 \cdot 10^{-3}T^2 + 1,33 \cdot 10^4 \cdot T^{-1} + 6,67T \lg T$	
1265-1378	$50\ 690 - 133,41T - 1,35 \cdot 10^{-3}T^2 + 1,33 \cdot 10^4 \cdot T^{-1} + 30,56T \lg T$	
1378-1538	$14\ 520 - 85,12T - 1,35 \cdot 10^{-3}T^2 + 1,33 \cdot 10^4 \cdot T^{-1} + 23,56T \lg T$	
1538-1977	$23\ 040 - 50,98T + 10,47T \lg T$	
	 $2\text{K}F + \text{Mg} = 2\text{K} + \text{MgF}_2$	
298-330,5	$5020 - 6,17T - 1,82 \cdot 10^{-3}T^2 + 0,59 \cdot 10^4 \cdot T^{-1} + 1,17T \lg T$	
330,5-923	$5120 + 20,12T + 3,74 \cdot 10^{-3}T^2 + 0,59 \cdot 10^4 \cdot T^{-1} - 10,13T \lg T$	
923-1048	$4630 + 2,87T + 2,51 \cdot 10^{-3}T^2 + 0,64 \cdot 10^4 \cdot T^{-1} - 3,76T \lg T$	
1048-1159	$48\ 350 - 76,50T + 2,51 \cdot 10^{-3}T^2 + 0,64 \cdot 10^4 \cdot T^{-1} + 8,65T \lg T$	
1159-1378	$43\ 000 - 143,05T - 1,35 \cdot 10^{-3}T^2 + 1,33 \cdot 10^4 \cdot T^{-1} + 33,85T \lg T$	
1378-1538	$6330 - 55,66T - 1,35 \cdot 10^{-3}T^2 + 1,33 \cdot 10^4 \cdot T^{-1} + 26,85T \lg T$	
1538-1775	$15\ 400 - 61,52T + 13,76T \lg T$	

Table 2

Card 6/6

Legend to Table 2: 1) Temperature

33029 R
S/096/60/000/011/010/018
E194/E384

26.5200

AUTHOR: Dubrovin, I.V., Candidate of Technical Sciences

TITLE: The Influence of the Temperature Factor on Heat Exchange

PERIODICAL: Teploenergetika, 1960, No. 11, pp. 69 - 74

TEXT: All the physical constants that determine the structure of a flow of liquid and its heat-exchange with a heating surface are functions of some power of the temperature. However, investigators often simplify the conditions to make experimentation easier and attempts are made to exclude the dependence of the physical constants on temperature. As strictly isothermal conditions cannot be maintained the changes in temperature affect the final results causing appreciable scatter. Some kind of governing or determining temperature may be introduced to help reduce this scatter; thus, some authors adopt the wall temperature, others relate the coefficient of thermal conductivity and the viscosity to the mean temperature of the boundary layer and the density to the flow temperature, and so on. Similarly, the Reynolds number may be assessed

Card 1/~~20~~ 6 X

The Influence of

33029 R
S/096/60/000/011/010/018
E194/E384

in different ways. Thus, various complications have arisen because experimenters have tried to simplify their conditions so as to exclude the temperature factor from the formulae. Most tests on convective heat transfer are carried out at low temperatures, small temperature differences and only slight deviations of temperature from the mean value and then the relationship between the Nusselt and the Reynolds numbers may conveniently take the following form:

$$Nu = cRe^n = c \left(\frac{w\eta d}{\eta} \right)^n \quad (1)$$

However, if the temperature varies over a wide range this is not satisfactory and the following formula should be used:

Card 2/~~10~~ 6

33029 R

S/096/60/000/011/010/018

E194/E384

The Influence of

$$Nu = cRe^n Pr^{0.33} \left(\frac{Pr_n}{Pr_{CT}} \right)^{0.25} \quad (2)$$

When it is necessary to introduce the temperature criterion
the following expression should be used:

$$Nu = cRe^n \left(\frac{T_{CT}}{T_n} \right)^p \quad (3)$$

Tests were made with bundles of tubes with the mean tube-wall
temperature ranging from 130 to 915 °C. The Reynolds number
ranged from 5 800 to 19 700. The results of using the
simplified formulae (1) and (2) are plotted in Figs. 1 and
2, which show, respectively, the total heat transfer of the

Card 3/~~20~~ 6

The Influence of

33029 R
S/096/60/000/011/010/018
E194/E384

first and second rows of a tube bundle in square arrangement with $s_1 = 2 d$ and $s_2 = 2.5 d$. It will be seen that the experimental points could be laid out on a number of different lines corresponding to different temperatures. In order to obtain a unique relationship between the Nusselt number and the other criteria the results were worked out by Eq. (3) and the results are plotted in Fig. 3. This figure plots the total heat-transfer from the tube bundles to the flow; here, it will be seen that the results lie very near to a single straight line. The characteristics used to determine the total heat-transfer coefficient entering into Eq. (3) for the tube bundles in question are given in Table 1. The first column of Table 1 gives the number of the row in the bundles and the lines correspond to, respectively, the first, second, third and fourth rows. Results published by other authors are then treated in a similar way and the great increase in the scatter of the results where this is done is shown. In solving heat-exchange problems when liquids flow in pipes or ducts of arbitrary shape, attempts are also made to avoid the temperature Card 4/~~10~~ C X

33029 R

S/096/60/000/011/010/018
E194/E384

The Influence of

criterion and as governing temperature it is sometimes recommended to adopt that which is given in technical calculations or which can most easily be determined. Difficulties arise because of the different physical properties of the various liquids that are used in practice. Test results for heat-transfer from tube walls to air flowing inside the tube are given in Fig. 6: the upper curves with marked scatter corresponding to expression (1) and the lower curve round which the experimental points lie closely being calculated by expression (3). Analysis showed that the temperature of either the heat-emitting or heat-receiving medium could be used equally well. Expression (1) of a simplified type can be applied over a narrow range of temperature change and only for the temperatures actually observed in the tests. For engineering calculations on industrial heat-exchange apparatus operating over a wide range of temperatures, Eq. (3) is recommended. If the Reynolds criterion is expressed in terms of the mean flow by weight the formula acquires a unified form. The procedure recommended for practical calculations

Card 5/~~12~~ 6.

X

33029 R
S/096/60/000/011/010/018
E194/E384

The Influence of

is valid with external flow across the surface and when liquid flows inside the tubes, whatever the direction of heat flow. There are 6 figures, 2 tables and 6 Soviet references.

ASSOCIATION: (Vsesoyuznyy nauchno-issledovatel'skiy institut metallurgicheskoy teplotekhniki (All-Union Scientific Research Institute of Metallurgical Heat Engineering)

Card 6/~~6~~ 6

DUBROVIN, I. V.

PA 18/49T25

USSR/Engineering
Stokers, Mechanical
Boilers

Dec 48

"Pneumatic Fuel Stoker for Small-Capacity Boilers,"
I. V. Dubrovin, Cand Tech Sci, VNIIT, 3 3/4 pp

"Stal'" No 12

All-Union Sci Res Inst of Fuel Utilization has
designed simple and reliable pneumatic stoker for
low-output boilers. This decreases labor and
number of firemen. Stoker recommended for use with
metallurgical furnaces. Three sketches.

18/49T25

4168. EXPERIMENT IN INSTALLATION OF VINIT TYPE PNEUMATIC FUEL
S-READER. Smirnov, AP., Mikrovia, IV and Kaplin, WM.
(Zh Ekon Topliva (Fuel Econ.), 1949, (12), 7-9). This type
was designed for converting hand fire boilers of about
7.5 sq. meters grate area. The s reader is installed
above the existing fire door, so that hand firing remains possible.
The fuel passes from an overhead hopper through a feeding
device, consisting of a variable speed drum with vanes,
on to a distributor plate. Air at 300-400 mm head of water
is fed to a series of 9-11 nozzles and blows the fuel from
this plate, over the fire. To ensure even distribution
over the grate area, the nozzles are fanned outwards slightly
and are in groups of 2 or 3 each with a valve for regulating
air pressure.

4168. METALLURGICAL LITERATURE CLASSIFICATION		EXTRACTED BY	
TYPE	CODE	EXTRACTOR	REVISER
1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16
17	18	19	20
21	22	23	24
25	26	27	28
29	30	31	32
33	34	35	36
37	38	39	40
41	42	43	44
45	46	47	48
49	50	51	52
53	54	55	56
57	58	59	60
61	62	63	64
65	66	67	68
69	70	71	72
73	74	75	76
77	78	79	80
81	82	83	84
85	86	87	88
89	90	91	92
93	94	95	96
97	98	99	100
101	102	103	104
105	106	107	108
109	110	111	112
113	114	115	116
117	118	119	120
121	122	123	124
125	126	127	128
129	130	131	132
133	134	135	136
137	138	139	140
141	142	143	144
145	146	147	148
149	150	151	152
153	154	155	156
157	158	159	160
161	162	163	164
165	166	167	168
169	170	171	172
173	174	175	176
177	178	179	180
181	182	183	184
185	186	187	188
189	190	191	192
193	194	195	196
197	198	199	200
201	202	203	204
205	206	207	208
209	210	211	212
213	214	215	216
217	218	219	220
221	222	223	224
225	226	227	228
229	230	231	232
233	234	235	236
237	238	239	240
241	242	243	244
245	246	247	248
249	250	251	252
253	254	255	256
257	258	259	260
261	262	263	264
265	266	267	268
269	270	271	272
273	274	275	276
277	278	279	280
281	282	283	284
285	286	287	288
289	290	291	292
293	294	295	296
297	298	299	300
301	302	303	304
305	306	307	308
309	310	311	312
313	314	315	316
317	318	319	320
321	322	323	324
325	326	327	328
329	330	331	332
333	334	335	336
337	338	339	340
341	342	343	344
345	346	347	348
349	350	351	352
353	354	355	356
357	358	359	360
361	362	363	364
365	366	367	368
369	370	371	372
373	374	375	376
377	378	379	380
381	382	383	384
385	386	387	388
389	390	391	392
393	394	395	396
397	398	399	400
401	402	403	404
405	406	407	408
409	410	411	412
413	414	415	416
417	418	419	420
421	422	423	424
425	426	427	428
429	430	431	432
433	434	435	436
437	438	439	440
441	442	443	444
445	446	447	448
449	450	451	452
453	454	455	456
457	458	459	460
461	462	463	464
465	466	467	468
469	470	471	472
473	474	475	476
477	478	479	480
481	482	483	484
485	486	487	488
489	490	491	492
493	494	495	496
497	498	499	500
501	502	503	504
505	506	507	508
509	510	511	512
513	514	515	516
517	518	519	520
521	522	523	524
525	526	527	528
529	530	531	532
533	534	535	536
537	538	539	540
541	542	543	544
545	546	547	548
549	550	551	552
553	554	555	556
557	558	559	560
561	562	563	564
565	566	567	568
569	570	571	572
573	574	575	576
577	578	579	580
581	582	583	584
585	586	587	588
589	590	591	592
593	594	595	596
597	598	599	600
601	602	603	604
605	606	607	608
609	610	611	612
613	614	615	616
617	618	619	620
621	622	623	624
625	626	627	628
629	630	631	632
633	634	635	636
637	638	639	640
641	642	643	644
645	646	647	648
649	650	651	652
653	654	655	656
657	658	659	660
661	662	663	664
665	666	667	668
669	670	671	672
673	674	675	676
677	678	679	680
681	682	683	684
685	686	687	688
689	690	691	692
693	694	695	696
697	698	699	700
701	702	703	704
705	706	707	708
709	710	711	712
713	714	715	716
717	718	719	720
721	722	723	724
725	726	727	728
729	730	731	732
733	734	735	736
737	738	739	740
741	742	743	744
745	746	747	748
749	750	751	752
753	754	755	756
757	758	759	760
761	762	763	764
765	766	767	768
769	770	771	772
773	774	775	776
777	778	779	780
781	782	783	784
785	786	787	788
789	790	791	792
793	794	795	796
797	798	799	800
801	802	803	804
805	806	807	808
809	810	811	812
813	814	815	816
817	818	819	820
821	822	823	824
825	826	827	828
829	830	831	832
833	834	835	836
837	838	839	840
841	842	843	844
845	846	847	848
849	850	851	852
853	854	855	856
857	858	859	860
861	862	863	864
865	866	867	868
869	870	871	872
873	874	875	876
877	878	879	880
881	882	883	884
885	886	887	888
889	890	891	892
893	894	895	896
897	898	899	900
901	902	903	904
905	906	907	908
909	910	911	912
913	914	915	916
917	918	919	920
921	922	923	924
925	926	927	928
929	930	931	932
933	934	935	936
937	938	939	940
941	942	943	944
945	946	947	948
949	950	951	952
953	954	955	956
957	958	959	960
961	962	963	964
965	966	967	968
969	970	971	972
973	974	975	976
977	978	979	980
981	982	983	984
985	986	987	988
989	990	991	992
993	994	995	996
997	998	999	1000

17
F
798. OPERATION OF FURNACES WITH VILIT TYPE PNEUMATIC FUEL SPREADERS.
Smirnov, I.P. and Dubrovina, IV. (Zn. Eksp. toplive (Fuel
Econ) May 1950, (5), 9-13). Details of successful results
obtained with the soviet spreader straker previously described
in Fuel Abstr., May 1950, n.6,T, 4168. (L)

137-1957-12-23262

The Effect of a Recovery Boiler on the Operation (cont.)

junction with an RB. The duration of the melting process is shortened by 9.5 percent. The consumption of conventional fuel is reduced by 23 percent. At the Magnitogorsk metallurgical combine the amount of steel skimmed was 12 percent greater in a open-hearth furnace that was equipped with an RB; the duration of the smelting process was reduced by 9 percent. The exhaust system must have at least a 25 percent excess in evacuation capacity.

Ye. N.

1. Boilers-Effect
2. Furnaces-Applications
3. Steel-Smelting

Card 2/2

11.9200

S/096/60/000/011/010/018

E194/E184

AUTHOR: Dubrovin, I.V. (Candidate of Technical Sciences)TITLE: The Influence of the Temperature Factor on Heat ExchangePERIODICAL: Teploenergetika, 1960, No 11, pp 69-74

TEXT: All the physical constants that determine the structure of a flow of liquid and its heat exchange with a heating surface are functions of some power of the temperature. However, investigators often simplify the conditions to make experimentation easier and attempts are made to exclude the dependence of the physical constants on temperature. As strictly isothermal conditions cannot be maintained the changes in temperature affect the final results causing appreciable scatter. Some kind of governing or determining temperature may be introduced to help reduce this scatter; thus some authors adopt the wall temperature, others relate the coefficient of thermal conductivity and the viscosity to the mean temperature of the boundary layer and the density to the flow temperature, and so on. Similarly, the Reynolds number may be assessed in different ways. Thus various complications have arisen because experimentors have tried to

JC

Card 1/4

8/096/60/000/011/010/018

E194/E184

The Influence of the Temperature Factor on Heat Exchange

simplify their conditions so as to exclude the temperature factor from the formulae. Most tests on convective heat transfer are carried out at low temperatures, small temperature differences and only slight deviations of temperature from the mean value, and then the relationship between the Nusselt and the Reynolds numbers may conveniently take the form of expression (1). However, if the temperature varies over a wide range this is not a satisfactory expression and formula (2) should be used. When it is necessary to introduce the temperature criterion expression (3) should be used. Tests were made with bundles of tubes with the mean tube wall temperature ranging from 130 to 915 °C. The Reynolds number ranged from 5800 to 19700. Other experimental details are given. The results of using the simplified formulae (1) and (2) are plotted in Figs 1 and 2 and it will be seen that the experimental points could be laid out on a number of different lines corresponding to different temperatures. In order to obtain a unique relationship between the Nusselt numbers and the other criteria the results were worked out by formula (3) and the results are plotted in Fig 3, from which it will be seen that the

Card 2/4

/c

S/096/60/000/011/010/018
E194/E184

The Influence of the Temperature Factor on Heat Exchange results lie very near to a single straight line. The characteristics used to determine the total heat transfer coefficient or entering into Eq (3) for the tube bundles in question are given in Table 1. Results published by other authors are then treated in a similar way and the great decrease in scatter of the results when this is done will be seen from the graphs of Figs 4 and 5, the first of which relates to flow over a single cylinder with the tube wall temperature ranging from 100 to 900 °C, and the latter to tests carried out with a constant tube wall temperature of 102-116 °C with an air flow temperature ranging from 150 to 455 °C. In solving heat-exchange problems when liquids flow in pipes or ducts of arbitrary shape, attempts are also made to avoid the temperature criterion, and as governing temperature it is sometimes recommended to adopt that which is given in technical calculations or which can most easily be determined. Difficulties arise because of the different physical properties of the various liquids that are used in practice. Test results for heat transfer from tube walls to air flowing inside the tube are given in Fig 6; the upper curve with marked Card 3/4

S/096/60/000/011/010/018
5194/E184

The Influence of the Temperature Factor on Heat Exchange scatter corresponding to expression (1), and the lower curve round which the experimental points lie closely being calculated by expression (3). Analysis showed that the temperature of either the heat emitting or heat receiving medium could be used equally well. Expression (1) of a simplified type can be applied over a narrow range of temperature change and only for the temperatures actually observed in the tests. For engineering calculations on industrial heat exchange apparatus operating over a wide range of temperatures, formula (3) is recommended. If the Reynolds criterion is expressed in terms of the mean flow by weight the formula acquires a unified form. The procedure recommended for practical calculations is valid with external flow across the surface and when liquid flows inside tubes whatever the direction of heat flow.

JC

There are 6 figures, 2 tables and 6 Soviet references.

ASSOCIATION: Vsesoyuznyy nauchno-issledovatel'skiy institut
Metallurgicheskoy teplotekhniki (All-Union Scientific
Research Institute of Metallurgical Thermo-Technics)

Card 4/4

DUBROVIN, I.V., kand.tekhn.nauk

Heat emission at high temperatures and in transverse flow around
bundles of pipe. Izv. vys. ucheb. zav.; energ. 3 no. 7:75-80
J1 '60. (MIRA 13:8)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut metallurgicheskoy
teplotekhniki. Predstavlena Uchenym sovetom etogo instituta.
(Heat--transmission)

DUBROVIN, I.V., kand. tekhn. nauk

Effect of the temperature factor on heat emission. Teploenergetika
? no.11:69-74 N '68. (MIRA 14:9)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut metallurgi-
cheskoy teplotekhniki.
(Heat--Transmission)

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

DUBROVIN, K.

Fertilizer spreaders. Tekhnov. MTS 17 no.24:1-5 D '56.

(MLRA 10:2)

(Fertilizer spreaders)

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

DUBROVIN, K. ofitser zapasa (Leningrad)

So that there may be more sports fans.... Voen. Znan. 41 no.5
40 My '65. (MIRA 18:5)

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

DUBROVIN, Klandija; KRAJINOVIC, Slobodan

Enterocolitis caused by pathogenic E. coli in children and adults.
Higijena, Beogr. 6 no.1:58-67 1954.

1. Bakteriolski institut Medicinskog fakulteta, Beograd
(COLITIS, bacteriol.
E. coli in enterocolitis)
(ENTERITIS, bacteriol.
E. coli in enterocolitis)
(ESCHERICHIA COLI, infect.
enterocolitis)

DUBROVAC, K., Dr.; KRAJINOVIC, S., dr.; ARSHENIJEVIC, K., m-r ph.;
KOSTIC, M., dr.

Single and combined effects of antibiotics in vitro on
conditionally pathogenic Escherichia coli. Voj. san. pregl.,
Beogr. 12 no.7-8:394-396 July-Aug 55.

1. Mikrobioloski institut Medicinskog fakulteta u Beogradu.
(ESCHERICHIA COLI, eff. of drugs on,
antibiotics, single & combined treatment in vitro (Ser))
(ANTIBIOTICS, eff.
on E. coli, single & combined treatment in vitro (Ser))

DUBROVIN, K. P.

"On Some Physico-Chemical Processes Occurring in Fissionable Materials Under
the Influence of Irradiation", by K. P. Dubrovin, S. T. Konobeyevsky,
B. M. Levitsky, L. D. Panteleyev, and N. F. Pravdyuk.

Report presented at 2nd UN Atoms-for-Peace Conference, Geneva, 9-13 Sept 1958

DUBROVIN, K. P.

AUTHORS: Konobayevskiy, S. T., Pravdyuk, N. F., Dubrovin, K. P., 89-1-4/29
Levitskiy, B. M., Pantelayev, L. D., Golyanov, V. M.

TITLE: Investigations of Structural Changes Occurring in an Uranium-Molybdenum Alloy by Neutron Irradiation. (Issledovaniye strukturnykh izmenenii, proiskhodящих v splave urana s molibdenom pod dejstviem naytronnogo obлучeniya).

PERIODICAL: Atomnaya Energiya, 1958, vol. 4, Nr 1, pp. 34-44 (USSR).

ABSTRACT: An U + Mo alloy with 9.05 weight percents of Mo is produced in a vacuum induction furnace. The melting charge is rolled out in a warm and cold state until a thickness of 0.1 mm is attained. From these foils the samples for measuring resistance and for radiographic investigations are produced. Before irradiation with neutrons, the samples are subjected to a homogenizing process of annealing (in the vacuum) at a temperature of 1000°C for three hours, after which they were cooled in the air.

After irradiation by neutrons the electric resistance was measured and the structure of the alloys was investigated radiographically and under the microscope.

The thermal treatment described made it possible to obtain samples

Card 1/2

89-144/29

Investigations of Structural Changes Occurring in an Uranium-Molybdenum Alloy
by Neutron Irradiation.

with the structure of an eutectoid $\alpha + \gamma'$, which has different sizes of grain.

It was found that the diffusion velocity leading to a homogenisation under the influence of irradiation in the annealed samples is inversely proportional to the square of the size of grain.

In the homogeneous sample (γ' - phase) irradiation causes a modification of properties and of structure, and already within a period of from 2 ~ 4 hours a maximum of effect is attained. This may be imagined to be something like "irradiation incandescence". In the γ' - phase also a re-orientation with transitions to a cubic lattice has been observed. This phenomenon occurs already during the first hours of exposure.

The size of the domain of the thermal peak and the energy liberated was determined at $2.5 \cdot 10^{-12} \text{ cm}^3$ and $\sim 2 \text{ MeV}$. These values are lower than those computed theoretically according to reference 2. There are 13 figures, 4 tables, and 4 references, 3 of which are Slavic.

SUBMITTED: September 11, 1957.

AVAILABLE: Library of Congress.
Card 2/2

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

APPROVED FOR RELEASE: 08/25/2000 CIA-RDP86-00513R000411410015-4"

DUBROVIN, L.

Operative accounting for the cost of meat production. Mias.ind.
SSSR 35 no.1:52-53 '64. (MIRA 17:4)

1. Leningradskiy ordena Trudovogo Krasnogo Znameni myasokombinat
imeni S.M.Kirova.

YEFIMOV, A.; TERAUD, V.; DUBROVIN, L.

Shortcomings in the method of calculating the cost of products.
Miss. Ind. SSSR 29 no. 4:42-44 '58. (MIRA 11:8)

1. Leningradskiy miasokombinat.
(Packing-house products--Costs)

DUBROVIN, L. D. (Aspirant)

"An Investigation of the Technological Factors in the Honing of Slot Apertures With Tempered Slots." Cand Tech Sci, Moscow Automotive Mechanics Inst, 30 Dec 54. (VM, 22 Dec 54)

Survey of Scientific and Technical Dissertations Defended at USSR Higher Educational Institutions (12)

SO: SUM No. 556, 24 Jun 55

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

DUBROVIN, L. I.

DUBROVIN, L. I.- "Geography of the Ice Cap in the Seas of the Near-Atlantic Arctic."
Molotov State U imeni A. M. Gor'kiy, Geology-Geography Faculty, Molotov, 1955
(Dissertations For the Degree of Candidate of Geographical Sciences)

SO: Knizhnaya Letopis' No. 26, June 1955, Moscow

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

DUBROVIN, L.I., kandidat geograficheskikh nauk.

Floating islands in Kama Reservoir, Nauka Press, Moscow, 1957.
(MLRA 10:3)

1. Molotovskiy gosudarstvennyy universitet im. A.M. Gor'kogo,
(Kama Reservoir--Islands)

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

DUBROVIN, L.I.; METABIN, Yu. M.

Transformation of the Kama, Geog. v shkole 21 no. 1:55-57 Ja-7 '58.
(MIRA 11:7)

(Kama Basin--Hydroelectric power stations)

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

DUBROVIN, L.I.

Opening the Lazarev Station. Inform. biul. Sov. antark. eksp.
no. 7:40-41 '59
(Lazarev(Antarctica))
(MIRA 13:3)

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

DUBROVIN, L. I.

Return of the Third Continental Expedition. Inform. biul. Sov.
antark. eksp. no.8:34-35 '59. (MIRA 13:3)
(Antarctic regions)

DUBROVIN, M.I.

Belgian orders awarded to members of the Soviet Antarctic
Expedition. Inform. biul. Sov. antark. eksp. no.8:35 '59.
(MIRA 13:3)
(Antarctic regions) (Rewards (Prizes, etc.))

DUBROVIN, L.I., kand. geograf. nauk

Scientific stations in Antarctic and subantarctic regions in 1957-1959. Inform. biul. Sov. antark. eksp. no.9:43-47 '59 (MIRA 13:3)

1. Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy institut.
(Antarctic regions--Observatories)

DUBROVIN, L.I., head, geograf. nachk.

Overland exploration traverses in Antarctica during the International
Geophysical Year. Inform. biul. Sov. antark. eksp. no. 10/5-8 '59
(MIRA 13:3)

1. Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy institut.
(Antarctic regions--Ice)

3(3)

SOV/26-59-3-31/47

AUTHOR: Dubrovin, L.I., Candidate of Geographic Sciences
(Leningrad)

TITLE: Where is the Cold Pole?

PERIODICAL: Priroda, 1959, № 3, p 115 (USSR)

ABSTRACT: The earth's Cold Pole seemed to be in the Verkhoyansk District in North Yakutia with absolute minimum temperatures of up to -69.8°C and in the Oymekon area 700 km southeast of Verkhoyansk where absolute minimum temperatures of up to -71°C were recorded. While the British "Northice" Station in Greenland and the American Amundsen-Scott Station in the Antarctic recorded very low absolute and mean minimum temperatures, the Soviet Antarctic station of Vostok ($78^{\circ}27' \text{S}/106^{\circ}52' \text{E}$), 3420 m above sea level, recorded -87.4°C on 25 Aug 1958 and a mean temperature of -71.6°C for the same month, and the station of Sovetskaya ($78^{\circ}24' \text{S}/106^{\circ}35' \text{E}$), 3570 m above sea level, recorded an absolute minimum of -86.8°C for one day in Aug 1958 and a mean -71.8°C for the same month. Consequently, the earth's Cold Pole

Card 1/2

SOV/26-59-3-31/47

Where is the Cold Pole?

apparently is situated in the southern hemisphere in the region of the geometric center of the continent.

ASSOCIATION: Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy institut (The Arctic and Antarctic Scientific Research Institute)

Card 2/2

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

DUBROVIN, L.I.; MATARZIN, Yu.N.; PECHERKIN, I.A.; NIKOLAEV, S.P., red.;
SYCHKIN, A.N., tekhn.red.

[Kama Reservoir] Kamakoe vedokhranilishche. Perm'. Permskoe
knizhnoe izd-vo, 1959. 159 p. (MIRA 13:6)
(Kama Reservoir)

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

ESTATE PLANNING

Geological. Anthracite & Anthomylonite Metamorphic rocks.
Paleontological. A distinctive fossil fauna, including
Acanthostega, Cystolepis, Eustreptorhynchus, *etc.*,
1000, species and subspecies, and numerous
molluscs, brachiopods, trilobites, *etc.*
Archaeological. At 1000 feet elevation, a large
prehistoric campsite, containing a great
number of stone tools.

Additional Examples of Artistic Effects. Special reference is made to the following:

FIG. 2. U.S. G. & G. C. 1900. BOSTON. BOSTON BRIDGE. 7
Scale 1:100,000. (Courtesy of U.S. G. & G. C.)

B. T. BELLINGER'S GUIDE TO THE BIRDS OF TEXAS

CULTURE AND CIVILISATION IN THE 19TH CENTURY

the first time in the history of the world, the people of the United States have been compelled to go to war with their own government.

THE JOURNAL OF CLIMATE

故其後人之爲也，皆不復能及。蓋其意在使後世知有是書，而不知其爲我所作也。

Consequently, he has some preparatory knowledge of the English language.

On the Nature and Origin of the Human Soul.

APPENDIX V. A Summary of Indian Practices as Indicated from Table

Mr. A.J. New-York Order of Perfection in the Faculty of Law

Henry F. B. See of Electro-kinetics and Building Materials.

Hannover, N. C. The Study of Automatic Contractions

BRIEF REPORTS

Lambert, A.P. The Problem of Construction of Trial Circles in
The Classification of
The Chemical Elements.

THE JOURNAL OF CLIMATE

Digitized by Google

the first time I have seen him. He is a man of great energy and enthusiasm.

સુરત પ્રદીપ

प्राचीन भारतीय विज्ञान एवं तकनीक

માર્ગ માનુષ

112

卷之三

卷之三

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

S/169/62/000/004/050/103
D228/D302

AUTHOR: Dubrovin, L. I.

TITLE: Air flows in the snow-firn stratum of the Lazarev shelf glacier

PERIODICAL: Referativnyy zhurnal, Geofizika, no. 4, 1962, 55, abstract 4V24 (Inform. byul. Sov. antarkt. ekspeditsii, no. 26, 1961, 13-14)

TEXT: Air flows, whose velocity is closely related to the wind speed in the near-ground layer of air, exist in the snow-firn stratum at a depth of not more than 15 m. Hole measurements showed that at a wind speed of 28 m/sec the velocity of air movement in the stratum's upper layers equals 1.4 cm/sec; it decreases with depth and becomes inappreciable at a depth of 15 m. The close connexion of the air circulation in the snow-firn stratum with the wind speed indicates that both phenomena are due to the same cause -- to the atmospheric pressure gradient. The coefficient of correlation equals 0.985. This phenomenon is reflected in the forma-

Card 1/2

Air flows in ...

S/169/62/000/004/050/103
D228/D302

tion of the glacier's temperature regime. The air circulation sometimes causes the formation of snow fountains and leads to the formation of a large amount of sublimation ice in the Lazarev glacier's numerous fissures. / Abstracter's note: Complete translation. /

Card 2/2

DUBROVIN, L. I., kand. geograf. nauk

Bottom relief in the area of Lazarev Station. Inform. biul.
Sov. antark. eksp. no. 32:27-28 '62. (MIRA 16:4)

1. Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy
institut.

(Lazarev Station, Antarctica—Ocean bottom)

DUBROVIN, L.I., kand.geograficheskikh nauk

Development of coastal ice in the area of Lazarev Station.
Inform. biul. Sov. antark. eksp. no.33:35-41 '62. (MIRA 16:2)

1. Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy
institut.
(Lazarev region, Antarctica—Ice)

DUEROVIN, L.

"Voice of the snow." Inform. biul. Sov. antark. eksp.
no. 33:49-50 '62. (MIRA 16:2)
(Lazarev Station, Antarctica—Snow)

DUBROVIN, L.I., kand. geograf. nauk

Brines in shelf ice. Inform. biul. Sov. antark. eksp. no.35:
35-38 '62. (MIRA 16:11)

1. Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy
institut.

BOLOTINA, F.Ye.; GAMBARYAN, Kh.P.; DENISOVA, G.A.; DUBROVINA, L.I.; KOZHINA, I.S.; KYURKCHAN, V.N.; MAKAROVA, T.I.; PAVLOVA, U.G.; REZVETSOV, O.A.; SMIRNOVA, V.V.; SURZHIN, S.N., kand. tekhn. nauk; TAMAMSHYAN, S.G.; TRUSOVA, S.A.; FILOGRIYEVSKAYA, Z.D.; CHINENOVA, E.G.; SHISHKINA, N.N.; IL'IN, M.M., zasl. deyatel' nauki RSFSR, doktor biol. nauk prof., red.; PRITYKINA, L.A., red.; ZARSHCHIKOVA, L.N., tekhn. red.

[Spice and aromatic plants of the U.S.S.R. and their use in the food industry] Priano-aromaticeskie rastenia SSSR i ikh ispol'zovanie v pishchevoi promyshlennosti. Moskva, Pishchepromizdat, 1963. 430 p. (MIRA 17:2)

DUBROVIN, L.I., kand.geograf.nauk

Dynamics of the Lazarev Shelf Ice. Inform.biul.Sov.antark.eksp. no.421
17-21 '63. (MIRA 17:1)

1. Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy institut.

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

DUBROVIN, L.I.; SYCHEV, M.A.

An obsolete manual. Okeanologija 3 no.5:949 '63. (MIRA 16:11)

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

DUBROVIN, L.I., kand. geograf. nauk; PETROV, V.N., insh.

Thermal action of an air current on thermometers measuring
the temperature of a snow layer in a hole. Inform. biul. Sov.
antark. eksp. no.39:15-19 '63. (MIRA 16:6)

l. Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy
institut.
(Lazarev station, Antarctica—Snow—Temperature)

DUBROVIN, L.I., kand.geograf.nauk; PETROV, V.N., inzh.

Accuracy of snow measurements in Antarctica. Inform.biul. Sov.antark.
eksp no.43:15-20 '63. (MIRA 17:1)

1. Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy institut.
(for Dubrovin).

SHESTERIKOV, N.P., kand.geograf.nauk; DUBROVIN, L.I., kand.geograficheskikh nauk

Tidal waves in the Lazarev Station region. Inform.biul.Sov.antark.
eksp. no.44:39-42 '63. (MIRA 17:4)

1. Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy institut.

DUBROVIN, L.I. (Leningrad)

"Soviet expeditions to the Antarctic in 1959-1961" by
A.V.Nudel'man. Reviewed by L.I.Dubrovin. *Natura* 52 no.4:121
'63. (MIRA 16:4)
(Antarctic regions-Russian exploration)
(Nudel'man, A.V.)

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

DUBROVIN, L.I.

An unfortunate error in the book by B.A. Savel'ev, Okeanologiya
4 no.3:535 '64 (NIRA 18:1)

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

DUBROVIN, L.I., kand.geograf.nauk; PETROV, V.N., insh.

Average height of the crust surface of Antarctica. Inform. biul.
Sov. antark. eksp. no.45:14-16 '64.

(MIRA 18:1)

I. Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy institut.

DUBROVIN, L.I., starshiy nauchnyy sotrudnik; KONOVALOV, G.V., mladshiy nauchnyy
sotrudnik

Dependence of snow accumulation on the topography in the region of
the Lazarev Station. Inform. biul. Sov. antark. eksp. no.45:29-32
'64. (MIRA 18:1)

1. Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy institut.

MIRSKIN, L.I., kand.zhigraf.srnik; MIRSKY, V.M., zhark.

Observations at scientific stations in the Antarctic during the
IGY and the IGSY. Inform.biul. Sov. antark.eksp. no.49:48-56 '64.
(MIRA 18:5)

I. Arkiticheskiy i antarkticheskiy nauchno-issledovatel'skiy
institut.

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

DUBROVIN, L.I., kand.geograf.nauk; SIMONOV, I.M., mladshiy nauchnyy sotrudnik

Tides in the Novolazarevskaya Station region. Inform.biul. Sov. antark.eksp. no.50:24-27 '64. (MIRA 18:5)

1. Arkticheskiy i antarkticheskiy nauchno-issledovatel'skiy institut.

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

Dubrovin, L. N.

112-1-1249

Translation from: Referativnyy Zhurnal, Elektrotehnika, 1957,
Nr 1, p. 194 (USSR)

AUTHOR: Dubrovin, L.N.

TITLE: Table Automat for the Control of Rollers of Bush Bearings
of Agricultural Machinery. (Nastol'nyy avtomat dlya
kontrolya rolikov vtulochnykh podshipnikov sel'skokhozyay-
stvennykh mashin). Scientific Research Institute of
Tractors and Agricultural Machinery (NIITraktorosel'-
khozmash)

PERIODICAL: Vestn.tekhn. inform.M-vo trakt. i s.-kh. mashinostr.
SSSR, 1956, Nr 4, pp.23-28.

ABSTRACT: Bibliographic entry

Card 1/1

DUBROVIN, L.N., insh.

Automatic machine for facing and removing chamfers on steel-aluminum thick-walled bushings. Mashinostroenie no.1:84-85
(MIRA 16:?)
Ja-F '63.

1. Nauchno-issledovatel'skiy institut tekhnologii traktornogo
i sel'skokhozyaystvennogo mashinostroyeniya.
(Machine tools)

DUBROVIN, L.N.

Automatic machine for mechanical and photoelectric control and
grading piston pins. Avt. i trakt. prom no.10:35-38 O '56.
(MIRA 10:1)

1. Nauchno-issledovatel'skiy institut traktorosel'khozmash.
(Pistons)

DUBROVIN, L.V.

Quantitative theory of critical control of gradient observations
of wind velocity in the lowest atmospheric layer. Trudy GGO
no.86:42-48 '58. (MIRA 11:11)
(Winds)

DUBREUIL, L.F.

PLATE I BOOK EXPOSITION	SCOTTISH BOOK TRADE
<p>Landsend. Glazebrook & Sons' <i>Observations</i> (Progress of Scottish universities with regard to the propagation of Naturalistic and Chemical Methods of Observation and Classification of animals). London, Edinburgh, and New York, 1859. 160 p. (Series I, Vol. 1-3.) 12mo. English printed.</p>	<p>Proprietary Agent: U.S.A.: Glazebrook & Sons' Ministry. Edinburgh, Glasgow, Liverpool, Birmingham, Manchester, &c.</p>
<p>Ed. (Title page). E. J. Pomeroy. <i>Condition of Geographical Sciences</i> Ed. (Index book). F. J. Gaskins. <i>Trade List</i>. 1, 7. Volume.</p>	<p>The publication is intended for members of working in offices of the Hydro-meteorological Service and in geophysical stations.</p>
<p>FRANCE. The publication is intended for members of the French Hydro-meteorological Service and in geophysical stations.</p>	<p>CONTACTS. This is a compilation of 11 articles, published by the Soc. of the Institute of the Hydro Geophysical Observatory, Paris A.I. Population, General statistics and the distribution of meteorological activities are devoted to special features in the field and its determinants. Other elements and the correlation between them and its determinants determine the methods of meteorological and astronomical observations and the procedures of their results. References are given at the end of each article.</p>

WANT TO ROCK YOUR TEAM?

land report. *Glossary of geological terms* (1926).
Voyaging methods, archaeological methodology & methodology of archaeology
(Problems of Archaeological Cooperation Institute and of Committee on Archaeology
of USSR Academy of Sciences, 1959, 1961 p. [Bortsev L.M.,
Korolev G.D.]).
pp. 500. 4to. Slip bound.
1,000 copies printed.

Sponsoring Agency: U.S.S.R. Glavgeologiya i Glavnoye Gosudarstvennoye Izdatelstvo
Gosudarstvennoye Naukovo Nauchnoye Izdatelstvo.

Address: 121, Pirogovskaya, Gospromgiz of Geographical Sciences;
16, 111-111a (post office), 21-21, Pirogovskaya, Tashkent. Ed. 1-3. Nal'yan.
Ed. 1 (first print). Ed. 2-3. (second print). Tashkent. Tashkent. Ed. 1-3. Nal'yan.
Ed. 4-5. (third print). Tashkent. Tashkent. Tashkent. Tashkent.

Price: The publication is intended for archaeological workers in various archaeological stations.
Price: 100 roubles. The publication is sold at the price of 100 roubles.
Coverage: This is a compilation of 11 articles published in the "Rev. Sov. of the USSR
Academy of the Marx-Cartesian Character" (1959, 1961) and in the "Glavgeologiya"
and the "Glavnoye Gosudarstvennoye Izdatelstvo" of the USSR Academy of Sciences.
Articles are devoted to special sources in the distribution of archaeological
remains and their formation conditions in the USSR and in Soviet Armenia. Some
articles analyze methods of materialistic and ethnohistorical researches.
The sources are given in the text and of each article.
Each article is preceded by a short summary.

卷之三

- Bailey, E.P., Radiation Belts of the Lower Surface of Antartica

Bailey, E.P., Horizontal Drifts of Snow in Antartica

Sabine, J.A., Special Features of the Formation and Certain Characteristics of the Snow Cover in Baffin's Gulf

Leopold, L.S., Air Temperature in Antartica

Leopold, L.S., Precipitation Measurements in Antartica

Fitzgerald, T.J. and T.J. Pfeiffer, A. Meteorological Observations in the Terra Novae Region, 1937-1938, During the International Geophysical Year

Leopold, L.S. and M.S. Johnson, Method of Measuring the Snow Cover

Leopold, L.S. and M.S. Johnson, Some Special Features in the Distribution of Relative Humidity in the Terra Novae Region

Douglas, J. and G. C. Smith, Control of the Observations of Daily Temperature by Means of Depth Thermometers

Pfeiffer, T.J., Characteristics of the Radiation Condition During Clear Weather

Fitzgerald, T.J., An Essay in Determining the Mean Monthly and Annual Amounts of Radiation

McFarlane, Library of Congress.

卷之三

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

DUBROVSKY, L.V.

Effect of local advection of moisture on the results of
evaporation observations. Trudy GGO no.108:91-97 '60.
(MIRA 13:11)
(Evaporation)

DUBROVIN, L.V.

Determination of the height of low clouds from ground data.
Meteor. i gidrol. no.9:52-55 S '62. (MIRA 15:8)

1. Kuybyshevskaya gidrometeorologicheskaya observatoriya.
(Clouds)

DUBROVIN, L., kand.geograf.nauk (Leningrad)

Decoding the riddles of the sixth continent. Nauka i zhyttia 12
no.6:46-47 Je '62.
(Antarctic regions) (MIRA 15:7)

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

DUBROVIN, L.V.

Determining the lower cloud boundary (below 300m from surface data. Trudy GGO no. 112:191-198 '63. (MIRA 17:5)

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

DUBROVIN, L.V.

Graphic method of determining the coefficient of thermal conductivity. Sbor. rab. Kuib. gidromet. obser. no.1:38-41 '64.

Derivation of the formula for determining the magnitude of the convective velocity W in the surface layer. Ibid.:42-44

Determining the derivative of wind velocity according to altitude for any condition according to data of gradient observations. Ibid.:45-46 (MIRA 17:12)

L ORI69-67 ENT(1) C

ACC NR: AR6016472

SOURCE CODE: UR/0124/65/000/012/B144/B144

24

AUTHOR: Dubrovin, L. V.

TITLE: Computation of all characteristics of the turbulent atmosphere for an altitude of one meter from standard gradient observations

SOURCE: Ref. zh. Mekhanika, Abs. 12B998

REF SOURCE: Sb. rabot Komsomol'sk. gidrometeorol. observ., vyp. 4, 1964, 45-55

TOPIC TAGS: atmospheric turbulence, weather forecasting

ABSTRACT: In calculating the characteristics of the turbulent atmosphere, the author based his work on that of A. S. Monin and A. M. Obukhov who showed that all these characteristics for a fixed altitude in the ground layer are functions of three parameters: dynamic velocity v^* , turbulent heat flow q and the quantity g/T . This ratio may be considered constant. The quantities v^* and q are expressed in terms of the derivatives $\partial u/\partial z$ and $\partial T/\partial z$. In his own work (sb. rabot Kuybyshevsk. gidrometeorol. observ., 1964, vyp. 1) the author showed that the following formulas are valid for an altitude of one meter under all conditions of temperature stratification and for all degrees of roughness in the underlying surface:

$$\frac{\partial u}{\partial z} = 0.724, \quad -\frac{\partial T}{\partial z} = 0.724$$

Card 1/2

L 08469-67

ACC NR: AR6016472

where $\Delta u = u_{10} + u_{\text{ref}}$, $\Delta t = t_{\text{ref}} - t_{10}$. Consequently, data of gradient observations (i. e. Δu , Δt and $\Delta \sigma$) may be used as a basis for calculating all characteristics of turbulence for an altitude of one meter. The author made these computations and compiled a table for the state of the turbulent atmosphere at an altitude of one meter as a function of measured values of Δu , Δt and $\Delta \sigma$. The resultant formulas were then verified on the basis of available experimental data published in the literature. Analysis showed that extensive experimental material confirms the author's formulas. Bibliography of 15 titles. S. I. Rudenko. [Translation of abstract]

SUB CODE: 04

Card 2/2

APPENDIX: Some peculiarities of eddy formation in the surface boundary layer

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

"APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4

ACC NM: AT6006496

corrections. Orig. ed. has: 8 tables, 13 formulae.

APPROVED FOR RELEASE: 08/25/2000

CIA-RDP86-00513R000411410015-4"

DUBROVIN, M.; MIKHAYLOV, V.

Comprehensive economic evaluation of the transportation of coal for power production. Rech. transp. 24 no. 4:18-19 '65.

(MIRA 18:5)

1. Glavnnyy spetsialist Gosudarstvennogo instituta proyektirovaniya i izyskaniya na rechnom transporto (for Dubrovin). 2. Zamestitel' nachal'nika Upravleniya gruzovoy i kommerscheskoy raboty Morskogo rechnogo flota (for Mikhaylov).